



SPECIFICATIONS

BTZ-42418-6

TYPE:-----	DIGITAL
DISPLAY:-----	4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
CHARACTER HEIGHT:-----	1.8" (45.72 mm)
VISIBILITY:-----	75 Ft. (22.86 METERS)
POWER REQUIREMENTS:-----	110-240V 50~60Hz (12vdc Switchig Power Supply)
FRAME:-----	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS:-----	6.25" x 64.25" x 1.38"
WEIGHT:-----	27 lbs.
OPERATING TEMP.:-----	-17° TO 180° F
HUMIDITY:-----	0% TO 95% NON-CONDENSING
OPERATING MODE:-----	SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.



ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.

1 SEC A YEAR ACCURATE (TCXO)

- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (**Standard**)
- AUTOMATIC DAY LIGHT CORRECTION (**Standard**)
- INFRARED REMOTE CONTROL (**Standard**)
- ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)

